

Model number	IQFU	-300	-PLUS	-AL	-N	-1
Description	Closed air flotation exercise platform	Stroke 300 mm	PLUS high Precision version	Aluminum alloy air flotation guide rail	Default	Incremental grating 1Vpp feedback

Model number	0	C1	-3	-Y	-Y
Description	The zero point is in the center of the trip	High flexible cable	Cable length 3 meters	There is a marble pedestal	Pressure protection switch

Name	Model number	Description
Single-axis air flotation exercise platform	IQFU	Closed air flotation exercise platform
Itinerary	-100	Stroke 100 mm
	-200	Stroke 200 mm
	-300	Stroke 300 mm
	-400	Stroke 400 mm
	-500	Stroke 500 mm
	-600	Stroke 600 mm
	-700	Stroke 700 mm
	-800	Stroke 800 mm
	-900	Stroke 900 mm
	-1000	Stroke 1000 mm
Accuracy level	-N	Standard value
	-PLUS	PLUS high Precision version
Air flotation rail type	-AL	Air flotation guide rail made of aluminum alloy
	-MA	Marble material air flotation guide rail
	-A	Ceramic material air flotation guide rail
	-S	Silicon carbide material air flotation guide rail
Electronic resolution	-N	default
	-0.3	Electronic resolution 0.3 nm
	-5	Electronic resolution 5 nm
Feedback method	-1	Incremental grating 1Vpp feedback
	-T	Incremental grating TTL feedback
	-ABS	Absolute grating feedback
Zero position	-L	The zero point is at the left limit of the trip
	0	The zero point is in the center of the trip (standard configuration)
	-R	The zero point is at the right limit of the trip
Cable management	-C1	High flexible cable
	-C2	Dust-free drag chain
Cable length	-3	Length 3 meters (standard configuration)
	-5	Length 5 meters
	-DZ	customized
Marble pedestal	-Y	There is a marble pedestal
	-N	No marble base (standard)
Pressure protection switch	-Y	Pressure protection switch (standard configuration)
	-N	Pressure-free protection switch